

SB-140 SKYLIGHT & WINDOW BUTYL SEALANT

DESCRIPTION: Flexible, one-part, easy to remove, elastomeric, butyl rubber sealant. Excellent for resealing and repairing leaks.

USES:

- | | |
|---|---|
| <p>Industries</p> <ul style="list-style-type: none"> • Construction • Architectural • Manufacturing | <p>Substrates</p> <ul style="list-style-type: none"> • Glass • Metal • Wood • Concrete • Cement • Masonry • Plastics • Fiberglass • Rubber material |
|---|---|

Not recommended for aquariums or terrariums.

APPLICATION: Interface and surfaces must be clean, dry and free of dust, dirt, oil and water proofing and release agents. Protective coatings on glass and aluminum surfaces must be removed with solvents. Wood surfaces must be sanded and cleaned. Use standard cartridge gun. Approved tools dipped in water for troweling will assure a complete filling of voids as well as provide maximum contact with sealant. Press nozzle into groove and apply steady even pressure to ensure that the joint is filled and no air is trapped.

SPECIFICATIONS:

VOC	248 g/l	
Tack-free Time	18-24 Hours	ASTM-C679 Test Method
Hardness, Shore A	70-80	TT-S-00230C Test Method
Staining	None	TT-S-00230C Test Method
Solids	80%	
UV Resistance	No discoloration	
Grade	Easy gun consistency	
Application Range	40° F to 100° F	

All values are typical at 75° F, 50% R.H. unless otherwise noted.
Federal Specifications TT-S-00230C used when applicable.

FEATURES:

- Stays soft and malleable
- Flexible
- Excellent adhesion
- Fast skinning
- Non-staining
- One part
- Weather resistant
- Paintable

BENEFITS:

- Easy to remove
- Allows for movement of dissimilar materials
- Bonds to substrates without priming
- Minimizes dirt and dust pickup
- Will not discolor or rust material
- Easy application
- Long service life
- Easy to match substrate

CLEANING: While uncured, remove excess material from tools with naphtha or mineral spirits. See cautions on cleaner labels.

SHELF LIFE: 12 months.

STORAGE: Unopened containers should be stored in a upright position in a cool, dry area. Rotate stock.

CAUTION: For industrial use only. Skin and eye irritant. Harmful if swallowed. Avoid contact with or breathing in of vapor and use adequate ventilation. Material on skin should be wiped and washed off with soap and water. For eyes, flush with water and seek medical attention. Keep away from open flames. SEE MATERIAL SAFETY DATA SHEET.

PACKAGING: 10.3 oz. tube, 52 gallon drum.

COLORS: White, gray.