

SB-2001 GENERAL PANEL ADHESIVE

DESCRIPTION: Waterproof panel and crating adhesive. Automatically shims and fills seams, small gaps and uneven wood surfaces.

USES:

Industries

- Construction
- Architectural
- Manufacturing

Substrates

- Wood
- Drywall
- Fiberglass
- Tile
- Metal
- Marble
- Mirrors

Not recommended for solvent sensitive plastics, foams, polystyrene or styrene containing plastic.

APPLICATION: Interface and surfaces must be clean, dry and free of dust, dirt, oil, frost, moisture and water proofing and release agents. Cut cartridge nozzle for desired bead size, puncture inner seal, and apply with steady pressure. Press panel to surface and repress. Make sure all panels are prefit and all cutouts have been made. Keep at room temperature before cold weather use.

SPECIFICATIONS:

VOC	380 g/l
Viscosity	Heavy Mastic
Application Range	40° F to 90° F
Panel Strength	Over 70 tons tensile shear strength on a 4'x8' panel

All values are typical at 75° F, 50% R.H. unless otherwise noted.
Federal Specifications TT-S-00230C used when applicable.

FEATURES:

- High strength
- Moisture resistant
- Freeze-thaw stable
- Excellent adhesion
- Paintable
- One part

BENEFITS:

- Durable bond to material
- Maintains bond in wet and moist conditions
- Excellent for cold weather applications
- Bonds to most substrates without priming
- Easy to match substrate
- Easy application

CLEANING: While uncured, remove material from tools with naphtha or mineral spirits. See cautions on cleaner labels.

SHELF LIFE: 12 months.

STORAGE: Unopened containers should be stored in a cool, dry area. Freeze-thaw stable. Rotate stock.

CAUTION: For industrial use only. Skin and eye irritant. Harmful if swallowed. Avoid contact with or breathing in of vapor and use adequate ventilation. Material on skin should be wiped and washed off with soap and water. For eyes, flush with water and seek medical attention.

SEE MATERIAL SAFETY DATA SHEET.

PACKAGING: 29 oz. cartridge, 52 gallon drum.

COLOR: Tan wood.