

SB-401 LOW VOC SEALANT

DESCRIPTION: One-step, high-strength, low VOC adhesive. Quick grab with fast tack strength. Bridges irregular surfaces and offers ease of panel alignment. Absorbs vibrations while stopping squeaks and deflection.

USES:

Industries

- Construction
- Architectural
- Flooring
- Manufacturing

Substrates

- Wood
- Metal
- Painted metal
- Pre-finished metal
- Fiberglass
- Wood veneers
- Wolmanized lumber
- Plastics
- Aluminum foil faced sheathing

Not recommended for solvent sensitive plastics, foams, polystyrene or styrene containing plastic.

APPLICATION: Interface and surfaces must be clean, dry and free of dust, dirt, oil, frost, moisture and water proofing and release agents. Cut cartridge nozzle for desired bead size, puncture inner seal, and apply. Press panel to surface and repress. Make sure all panels are prefit and all cutouts are made. Apply only as much adhesive as can be covered with panel in 20 minutes.

SPECIFICATIONS:

VOC	<50 g/l
Cure Time	24 Hours
Viscosity	Heavy Mastic
Panel Strength	Over 130 tons tensile shear strength on a 4'x8' panel

FEATURES:

- Excellent adhesion
- Fast cure
- Moisture resistant
- High strength
- One part
- Paintable

BENEFITS:

- Bonds to most substrates without priming
- Expedited production
- Maintains bond in wet and moist conditions
- Durable bond to material
- Easy application
- Easy to match substrate

CLEANING: While uncured, remove material from tools with naphtha or mineral spirits. See cautions on cleaner labels.

SHELF LIFE: 12 months.

STORAGE: Unopened containers should be stored in a cool, dry area at less than 100° F in an upright position. Freeze-thaw stable. Rotate stock.

CAUTION: For industrial use only. Skin and eye irritant. Harmful if swallowed. Material on skin should be wiped and washed off with soap and water. For eyes, flush with water and seek medical attention.

SEE MATERIAL SAFETY DATA SHEET.

PACKAGING: 10.3 oz. cartridge, five gallon pail, 50 gallon drum.

COLOR: Natural sand.

All values are typical at 75° F, 50% R.H. unless otherwise noted.
Federal Specifications TT-S-00230C used when applicable.