

## SB-540 SERIES EVERSEAL TAPE

**DESCRIPTION:** A solventless, high bond, heavy mass, structural grade pressure sensitive tape. Cures immediately and remains permanently flexible.

### USES:

- | Industries  | Substrates   |
|---|--|
| <ul style="list-style-type: none"><li>• Automotive</li><li>• Manufacturing</li><li>• Construction</li></ul> | <ul style="list-style-type: none"><li>• Metal</li><li>• Plastic</li><li>• Rubber</li><li>• Polyethylene sheeting</li><li>• Films</li></ul> |

**APPLICATION:** To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

### FEATURES:

- Clean, easy-to-use alternative to brush or gun applied adhesives
- Replaces rivets and welds
- Excellent bond strength
- Non-hardening
- No cure time
- Solvent free, no fumes

### BENEFITS:

- Less mess and quick, simple installation
- Time and cost effective
- Strong grip to a variety of surfaces
- Permanent flexibility
- Expedited production
- Safe

**STORAGE:** Tape should be stored at 70°F (21°C) with 50% relative humidity.

**SHELF LIFE:** 18 months.

**CAUTION:** For industrial use only.

**DIMENSIONS:** SB-544: .040" X .75" X 66'  
Other sizes available upon request

**COLOR:** Translucent.

### SPECIFICATIONS:

Tensile strength	150 psi
Elongation	1000%
Peel adhesion	44 pli
Application temperature range	50°F to 100°F (10°C to 38°C)
Functional temperature range	-30°F to 150°F (-1°C to 65°C)