

### PS-800 SUPER BONDING CONSTRUCTION ADHESIVE

**DESCRIPTION:** Easy to use, fast curing, one part, heavy-duty sealant. Provides permanent high strength bonds.

**USES:**

**Industries**

- Construction
- Architectural
- Concrete
- Roofing

**Substrates**

- Wood
- Plywood
- Wolmanized lumber
- Concrete
- Metals
- Brick
- Gypsum
- Plaster

Not recommended for solvent sensitive plastics, foams, polystyrene or styrene containing plastic.

**APPLICATION:** Interface and surfaces must be clean, dry and free of dust, dirt, oil, frost, moisture and water proofing and release agents for best results. Cut cartridge nozzle at slant and puncture inner seal, apply bead size as desired. Apply a continuous 1/4" diameter bead of adhesive to furring strips or framing studs top and bottom. Positioning and alignment should be done within 20 minutes with reduced nailing and bowing on bowed panels. Always prefit panels before applying adhesives and extinguish all igniters as the solvents used in this adhesive are flammable.

**SPECIFICATIONS:**

VOC	<370 g/l	34% by weight
Cure Time	6-8 Hours	Using 1/8" Bead
Tensile Strength	100,000 PSI on 4'x8' panel	ASTM-D412 Test Method

All values are typical at 75° F, 50% R.H. unless otherwise noted.  
Federal Specifications TT-S-00230C used when applicable.

**FEATURES:**

- High-strength
- Fast cure
- Synthetic rubber base
- One part
- Moisture resistant
- Excellent adhesion

**BENEFITS:**

- Durable bond to material
- Expedited production
- Deadens sound, eliminates squeaking
- Ready to use, labor cost reduction
- Maintains bond in wet and moist conditions
- Bonds to most substrates without priming

**CLEANING:** While uncured, remove excess material from tools with mineral spirits. See cautions on cleaner labels.

**SHELF LIFE:** 12 months.

**STORAGE:** Unopened containers should be stored upright in a cool, dry area at room temperature, 50% R.H. Rotate stock.

**CAUTION:** For industrial use only. Skin and eye irritant. Harmful if swallowed. Avoid contact with or breathing in of vapor and use adequate ventilation. Material on skin should be wiped and washed off with soap and water. For eyes, flush with water and seek medical attention. Only use in well ventilated areas away from all flames and sparking equipment.

SEE MATERIAL SAFETY DATA SHEET.

**PACKAGING:** 29 oz. tube.

**COLOR:** Bronze.

Revised:04/02/07