

PS-800 SUPER BONDING ADHESIVE LOW VOC

Page Number: 1/6
Version Number: 1
Revision Date: 09/22/08

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: PS-800 SUPER BONDING ADHESIVE VOC COMPLIANT FORMULATION

Company Name: SUREBOND
2801 International Lane
Madison, WI 53704
Phone: (608) 237-7554

Emergency Phone (24 hour): CHEMTREC
(800) 424-9300

Chemtrec (outside USA): (703) 527-3887

SECTION 2 - INGREDIENT AND HAZARD INFORMATION

NFPA Hazard Codes: Health: 2 Fire: 3 Reactivity: 0

NOTE: Repeated and prolonged overexposure to the mixture of solvent(s) listed in Section 3 can result in systemic effects including permanent brain, nervous system, liver and kidney damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

EMERGENCY OVERVIEW: DANGER: EXTREMELY FLAMMABLE. VAPOR HARMFUL. CONTAINS ACETONE, METHYL ACETATE HEXANE. Vapors can cause flash fire. Vapors can ignite explosively. Prevent buildup of vapors by opening all windows and doors to create cross-ventilation. Keep away from heat, sparks, and open flame. Do not smoke. Turn off stoves, heaters and sparking electric motors. Keep container tightly closed when not in use. Avoid prolonged breathing of vapor. KEEP OUT OF THE REACH OF CHILDREN. Product is a beige, medium viscosity mastic.

Routes of Entry:

Ingestion: YES
Inhalation: YES
Skin: YES
Eye: YES

Effects of Exposure:

Eyes: May cause severe eye irritation.
Skin: Prolonged or repeated contact can cause moderate irritation, defatting and dermatitis.
Inhalation: Avoid breathing vapor or mists. May cause headaches or dizziness. High vapor concentrations are irritating to the nose, throat and lungs and can cause systemic effects. Vapors can readily accumulate in confined or poorly ventilated areas.
Ingestion: Ingestion is not a probable route of exposure. Harmful if swallowed.

Medical conditions aggravated by exposure: Preexisting neurological conditions, skin disorders and respiratory disease.

Reproductive toxicity: This product has not been evaluated for reproductive toxicity.

PS-800 SUPER BONDING ADHESIVE LOW VOC

Page Number: 2/6
Version Number: 1
Revision Date: 09/22/08

Target organs: Prolonged or repeated overexposure may cause eye, skin, respiratory system, central nervous system, peripheral nervous system, liver and kidney damage.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient Name	CAS Number	Percent
Methyl acetate	79-20-9	17.62
Acetone	67-64-1	3.70
Hexane	110-54-3	2.53

OSHA PELs & ACGIH TLVs are listed in Section 8 where applicable.

SECTION 4 - FIRST AID MEASURES

Eyes:	Hold eyelids apart and flush with plenty of water for at least 15 minutes. Seek medical attention.
Skin:	Wash thoroughly with soap and water. Contact a physician if irritation develops or persists.
Inhalation:	Remove to fresh air. If difficulty persists seek medical attention.
Ingestion:	Call poison control center immediately. Follow their specific instructions. Do not induce vomiting.

SECTION 5 - FIRE FIGHTING MEASURES

Flammability Class (OSHA):	I B
Flash Point:	<0° F Setaflash
Explosive Range:	LEL: 1% UEL: 16%

Flammable liquid. Can form explosive mixtures at temperatures at or above the flashpoint.

Extinguishing Media:	Use alcohol foam, carbon dioxide, or dry chemical when fighting fires involving this product.
Hazardous Combustion Products:	Oxides of carbon may be released during combustion.
Fire Fighting Procedures:	Wear a NIOSH approved self contained breathing apparatus. Wear appropriate personal protective equipment. Use water spray or fog to cool fire exposed containers. Closed containers may explode when exposed to extreme heat.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Containment techniques:	Use inert absorbent to dike the spill. Keep away from drains.
-------------------------	---

PS-800 SUPER BONDING ADHESIVE LOW VOC

Page Number: 3/6
Version Number: 1
Revision Date: 09/22/08

Clean up: If possible pump liquid into an approved container or spread absorbent over spill and shovel (use non-sparking equipment) product/absorbent mixture into an approved container. If product has dried, scrape up and place in an approved container.

Emergency measures: Isolate hazard area. Keep unnecessary and unprotected personnel from entering area. Wear all appropriate personal protection equipment (PPE) (See Section 8).

SECTION 7 - HANDLING AND STORAGE

Handling: Avoid breathing vapors from the headspace of containers. Keep containers closed when not in use. Use only in well ventilated areas. Follow all MSDS/label precautions even after container is emptied. Containers may retain product residues and vapors.

Storage: Keep away from sources of ignition. Store large quantities in buildings designed for storage of NFPA Class 1-B flammable materials.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
Methyl acetate	200.00 PPM	N/est	250.00 PPM	N/est	200.00 PPM
Acetone	500.00 PPM	N/est	1000.00 PPM	N/est	1000.00 PPM
Hexane	50.00 PPM	N/est	N/est	N/est	500.00 PPM

Engineering controls: Use local exhaust as needed to maintain occupational exposure limits. Maintain standard plant ventilation.

Other: Facilities storing or utilizing any chemical should be equipped with an eyewash facility and a safety shower.

Personal Protective Equipment:

Respiratory Protection: Where exposure limits may be exceeded select a NIOSH approved respirator with appropriate Protection Factor and cartridge for the specific containments. Follow requirements for respiratory protection in OSHA 1910.134.

Eye Protection: Chemical splash goggles (ANSI Z87.1 or approved equivalent).

Skin Protection: Where skin contact can occur, wear impervious gloves.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form: Mastic
Appearance/color: Beige
Odor: Solvent
Solubility (in water): Nil

PS-800 SUPER BONDING ADHESIVE LOW VOC

Page Number: 4/6
Version Number: 1
Revision Date: 09/22/08

pH Value, +/- .3:	N/A
Boiling Range:	133° F - 154° F
Evaporation Rate:	Faster than n-Butyl Acetate
% Volatile:	24.%
Specific Gravity:	1.25
VOC:	<50 g/L

SECTION 10 - STABILITY AND REACTIVITY

Stability:	This product is stable.
Hazardous Polymerization:	Hazardous polymerization will not occur.
Conditions to Avoid:	Keep away from heat, spark, open flames and any ignition source.
Hazardous Decomposition Products:	Oxides of carbon may be released during combustion.

SECTION 11 - TOXICOLOGICAL INFORMATION

Carcinogenicity: IARC: No NTP: No OSHA: No

Adverse health effects are not expected from normal use of this product. The following is toxicological information for individual components.

Hexane - acute:

Ingestion of hexane can cause nausea, vomiting, stomach pain and diarrhea. Hexane can irritate the skin and the eyes. Acutely, the most common toxic effects are central nervous system depression and chemical pneumonitis resulting from aspiration into the lungs following ingestion.

Hexane - chronic:

Dermal irritation and central nervous system depression accompanied by peripheral nervous system damage (polyneuropathy) are common traits of sustained overexposure.

Methyl acetate:

Breathing small amounts of methyl acetate during normal handling may cause irritation to the mucous membranes of the nose, throat and lungs. Excessive inhalation can cause central nervous system depression which could include dizziness, drowsiness, weakness, fatigue, nausea, headache and unconsciousness. Methyl acetate is a moderate eye irritant and can cause stinging, redness and swelling of the eyes. It is also a skin irritant and prolonged contact will result in defatting and redness of the skin which could lead to dermatitis. Ingestion of methyl acetate can cause nausea, vomiting and diarrhea.

Acetone - acute:

Acetone has a low order of acute and inhalation toxicity. Acetone is a slight skin irritant and moderately severe eye irritant. Excessive inhalation can cause headache, drunkenness and weakness.

Acetone - chronic:

Kidney damage and anemia can result from sustained high level exposure. Acetone is reported to potentiate the liver toxicity of chloroform.

PS-800 SUPER BONDING ADHESIVE LOW VOC

Page Number: 5/6
Version Number: 1
Revision Date: 09/22/08

SECTION 12 - ECOLOGICAL INFORMATION

This formulation has not been tested for environmental effects.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of following local, state, and federal regulations.

Container Disposal: Dispose of following local, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION (not all sizes available)

Ground Transport (DOT) -

Units less than 5 L (1.3 gallons liquid) i.e. 10 oz., 28 oz., 1 gal.

UN Number: None
UN Pack Group: Not applicable
UN Class: ORM-D
Shipping Name: Consumer Commodity

Air Transport -

Units less than 5 L (1.3 gallons liquid) i.e. 10 oz., 28 oz., 1 gal.

UN Number: ID8000
UN Pack Group: Not applicable
UN Class: 9
ICAO/IATA Class: 9
Shipping Name: Consumer Commodity

Units of 29 oz. to 1 gallon sizes of this product or any shipment of this product in a 1 gallon to 5 gallon container

UN Number: UN1133
UN Pack Group: III
UN Class: 3
ICAO/IATA Class: 3
IMDG Class: 3
Shipping Name: Adhesives containing a Flammable Liquid

Packaging may not be approved for shipping by air. Please contact Surebond, Inc. for further information.

Maritime -

Units less than 5 L (1.3 gallons liquid) i.e. 10 oz., 28 oz., 1 gal.

UN Number: UN1133
UN Pack Group: 3
UN Class: 3
IMDG Class: Adhesive, 3, UN1133, PG III, LTD. QTY.

PS-800 SUPER BONDING ADHESIVE LOW VOC

Page Number: 6/6
Version Number: 1
Revision Date: 09/22/08

Shipping Name: Adhesive
EMS Code: F-E, S-D

SECTION 15 - REGULATORY INFORMATION

Sara Title III Section 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Chemical Name	CAS Number	Percent
Hexane	110-54-3	2.53
Toluene	108-88-3	Trace

PROP 65 (TERATOGEN)

WARNING: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

Ingredient Name	CAS Number	Percent
Toluene	108-88-3	Trace

TSCA (Toxic Substances Control Act Inventory):

All components of this product are listed on the TSCA inventory except as exempted.

PENNSYLVANIA:

Hazardous components required to be listed at 1% or more:

acetone; 2-propanone; 67-64-1

methyl acetate; 79-20-9

kaolin clay; kaolin, 1332-58-7

hexane; 110-54-3

limestone; 1317-65-3

Non-hazardous ingredients required to be listed at 3%:

petroleum hydrocarbon resin 68131-87-3

NEW JERSEY:

methyl acetate 79-20-9, hexane 110-54-3, acetone 67-64-1, petroleum hydrocarbon resin 68131-87-3, clay 1332-58-7

SECTION 16 - OTHER INFORMATION

DISCLAIMER:

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method or apparatus mentioned. User must make his/her own investigation to determine the suitability of the information or products for his/her particular purpose, for the protection of the environment and the health and safety of the users of this material.

Abbreviations:
N/A = Not Applicable
N/D = Not Determined
N/Est = Not Established