





# SUREBOND







Joint Stabilizers ◊ Sealers ◊ Cleaners ◊ Adhesives

## ADHESIVE & SEALANT SOLUTIONS

SUREBOND PRODUCT	DESCRIPTION	BEST APPLICATIONS	ADVANTAGES	SIZES	COLORS
<b>SB-12 METALBOND</b> 	High strength, heavy-duty, metal sealant. Forms water resistant bonds.	Steel, aluminum, painted metals, galvanized metals, refrigeration, plumbing, HVAC.	Color blends well with metals to give cohesive look. Paintable.	10.3 oz. tube	Aluminum gray
<b>SB-140 SKYLIGHT &amp; WINDOW SEALANT</b> 	One-part, single application butyl. Remains permanently flexible.	Doors, windows, skylights, masonry, metal, wood, metal roof seams.	Recommended for Lexan, polycarbonate and acrylic skylights.	10.3 oz. tube 52 gallon drum	White, gray
<b>SB-190 EVERSEAL</b> 	Versatile, one-part, pick proof sealant. #1 for snowguard adhesion.	Plastic, metal, fiber-glass, vinyl, wood, painted metals, specialty finishes such as Kynar®.	Elongation up to 500%. Tensile strength of 2,000 psi.	10.3 oz. tube 50 gallon drum	Translucent
<b>SB-400 STRUCTURAL ADHESIVE</b> 	High-strength, waterproof structural adhesive.	Sub-flooring, decking, foil backed materials, concrete, wood, metal.	Absorbs vibrations. Freeze-thaw stable.	29 oz. tube 50 gallon drum	Aluminum gray, white (drum only)



Surebond offers several choices for environmentally safe products. While there is no single definition for what is environmentally safe, we take the lead from organizations who specialize in green building, such as the NAHB. All the products below are rated at VOC (volatile organic compounds) of 200 g/L or less for construction adhesives and 60 g/L or less for sealants.

SUREBOND PRODUCT	DESCRIPTION	BEST APPLICATIONS	ADVANTAGES	SIZES	COLORS
<b>SB-1 POWERSEAL</b> 	Fast setting, heavy duty urethane sealant. VOC compliant.	Roofing, flashings, masonry walls & concrete, plastics, composite boards.	Excellent durability. Compare to Sonneborn NP-1.	10.3 oz. tube 20 oz. sausage 50 gal. drum	Gray
<b>SB-10 PAVER BOND</b> 	Quick curing, high strength, structural grade adhesive. VOC compliant in 10.2 oz.	Retaining walls and caps, concrete, coping systems, masonry, brick. Also treated lumber, gypsum and fiberglass.	Can be applied in moist, cool environments. Freeze-thaw stable. Naturally shims and levels.	10.2 oz. tube (VOC compliant), 28 oz. tube	Sand
<b>SB-188 HIGH TEMP SILICONE SEALANT</b> 	Non-flammable, high temperature silicone sealant. VOC compliant.	Heating systems, furnaces, automotive applications, HVAC.	Unaffected by UV exposure, cold weather or moisture. USDA approved. 350 psi tensile strength.	10.3 oz. tube	Clear, black, white, aluminum, red
<b>SB-299 POWERSEAL 2</b> 	Rapid curing urethane sealant. VOC compliant.	Polystyrene, concrete, glass, wood, masonry, painted metals, OSB board, marine use.	Tack free in 20 minutes. Tensile strength of 600 psi.	10.3 oz. tube	White, gray
<b>PS-800 SUPER BONDING ADHESIVE</b> 	Fast curing, high-strength construction adhesive. Regular and VOC compliant formulas.	Wood, plywood, wolmanized lumber, concrete, metals, plaster and gypsum.	Durable bond to most building surfaces. Can be applied at 0 degrees F.	10.5 oz. tube (VOC compliant), 29 oz. tube	Tan
<b>SB-1800 EVERFLEX BONDAPRENE</b> 	Non-flammable, spot-weldable sealant. VOC compliant.	Metal, wood, glass, plywood, most plastics.	Quick curing. -20°F to 140°F application temp. Tensile strength of 360 psi.	10.3 oz. tube 48 gallon drum	Clear

Toll Free: 877-843-1818 ◊ Fax: 608-237-7558 ◊ Email: [adhesivesales@surebond.com](mailto:adhesivesales@surebond.com)  
 2801 International Lane ◊ Madison, WI 53704